

Hydro-Pure

Dental Water Technology "Pure and Simple"



Hydro-Pure Purified Water System Features & Benefits

- Green product, with no plastic bottles disposed in landfill
- Endless flow of purified water to your dental office
- Fill autoclaves and clean water bottles with distilled grade water, quickly and effortlessly from the Hydro-Pure faucet plumbed directly to the Sterilization-Center
- Reduces costly maintenance of dental delivery systems
- Eliminates the time and hassle of buying distilled water
- ADA compliant
- Maintenance friendly



Dental Water Technology “Pure and Simple” Complete System Specifications

Complete System

Hydro-Pure

Faucet Specification	Quality (000-005 TDS ppm)
Maximum Operating Temperature	100° F
Minimum Operating Temperature	40° F
Maximum Operating Pressure	100 psi
Minimum Operating Pressure	35 psi
Optimal pH Range	6.5 – 8.5
Maximum Total Dissolved Solids (TDS)	1000 ppm
Maximum pH Range	3 - 11
Maximum Influent Hardness	10 gr/171 ppm
Maximum Influent Manganese	0.05 ppm
Maximum Influent Iron	0.1 ppm
Maximum Influent Hydrogen Sulfide	0.00
Maximum Influent Chlorine/Chloramine	3 ppm
Maximum Daily Output (12 hours)	12 gal (45.36 L) (WQA NSF 58 Standard)
Pre-Filter Element Service Life	1 year max
Cartridge, Carbon Service Life	1 year max
Cartridge, Deionization Resin Service Life	1 year max
Cartridge, RO Module Service Life	2 year max
Tank Dimensions (Dia x H)	11" D X 13.7" H
System Dimensions (W x H x D)	15' x 15.5 x 6"
Approximate Shipping Weight	27 lbs. – (1 Cartons)

